



Cascade

Manufacturers & Suppliers of Pipe Fittings
for the Water and Gas Industries

WAGA End Load Coupling

The WAGA End Load Coupling for PE, PVC, Cast Iron, Ductile Iron, Steel and Asbestos Cement Pipes, ideal for making connections in pipe networks.

This fitting offers a wide tolerance and easy install making tight spaces easier to work in.

The WAGA has excellent end load and permissible working pressure ratings of 16 bar, and will bite onto soft or hard pipes, Inserts are recommended for extra performance on PE Pipe.



Materials

Ductile iron GGG-45 body
EPDM to BS EN 681-1 Gasket
Bolts, Nuts and washers: A2 Stainless Steel
ANSI 304
Epoxy WRAS approved Resicoat 9000 R4

Part No	Nominal Bore	Range	Weight KG
CEL050	2"/50	46-71	5.7
CEL065	60/65	63-90	6.4
CEL080	3"/80	84-105	6.5
CEL100	4"/100	104-132	8.2
CEL125	5"/125	132-155	12.8
CEL150	6"/150	154-192	15
CEL200	8"/200	192-232	18
CEL225	9"/225	230-268	29.1
CEL250	10"/250	267-310	30
CEL300	12"/300	315-356	41
CEL350	14"/350	353-393	48
CEL400	16"/400	393-433	59